

Stilan® Heavy Duty Non Slip Tiles

Conforming to IS (13801-1993)

TECHNICAL DATA COMPOSITION

Topping Cement, pigment, filler, Stilan® abrasion resistance grain

Backing Grey cement, Stone grit/ Dust



Topping Layer - 6mm to 8mm (IS spec 5mm to 6mm) Backing Layer - 17mm to 19mm



Wet Transverse Strength Above 3N/mm2



Below 3.5 mm





Standard Size 20cmx20cm, 25cmx25cm, 30cmx30cm, 40cmx40cm



Colours

Thickness For Flooring Tile General use 25mm, Heavy Duty 30mm

Abrasion Resistance Impact Resistance

General Purpose Maximum 3.5mm

Grey, Red, Fawn, Dark Green, Dark Brown, Black, Silver Grey, Crazy Green, Yellow, Cream, White



STILAN®

Non-Slip Tiles

The best non-slip tiles for Heavy-duty & Extra Heavy-duty floors.



Bharat Floorings & Tiles (Mumbai) Pvt.Ltd.

32, Mumbai Samachar Marg, Next to Stock Exchange, Fort, Mumbai 400 023 Tel: 91 (22) 4057 4400, 23, 44 E-mail: info@bharatfloorings.com Website: www.bharatfloorings.com

Different Sizes and Designs of Tiles



Rock Finish 30x30 cms



25x25 cms



Crocodile 20x20 cms



40x40 cms



Pebbled Finish 40x40 cms





30x30 cms

Various Shapes, Steps and Risers



Step 32.5 X 20 cms



Step 30 x 30 cms



Curved Skirting / Vata



Cellular 30x15 cms

Different Sizes and Designs of Tiles





25x25 cms



100 Checks 25x25 cms



Straight Fluted 25x25 cms

4 Ribbed

25x25 cms

25 Checks

25x25 cms



Half Cross Fluted 25x25 cms



Amarson 30x30 cms



Ethnic 25x25 cms

25x25 Circular cms





Broad Fluted 30x30 cms

Colour Chart JAISALMER **TERRACOTTA** CHOCOLATE

These are base colours without Chips These colours are indicative. Cement colour shades will be slightly different from printed colours. Though we use the finest ingredients and blend these with utmost care, variations in the shades of raw material can lead to variations in the shades of raw materials can lead to variations between batches. These are the hallmark and charm of handcrafted products. Note: Blue and green colours are not recommended for use in sunlight.







